


PRODUCT DATASHEET

M 605 P 60 UM -SF-F3

PV PANELS P-TYPE MONOFACIAL SILVER | PERC monofacial photovoltaic panels with silver frame



Areas of application

- Utility installations
- Commercial and industrial installations
- Residential installations

Product benefits

- 12-years of product guarantee, 25-years of linear power output guarantee
- Limited PID-effect (potential induced degradation) thanks to strict quality control in production process
- Very low yearly degradation of the cells thanks to the better resistance to high temperatures
- Durable design and highest production standards guarantees operational reliability and quality

Product features

- Original Stäubli MC4 EVO 2 connectors
- Available in a long cable version
- Frame made of anodized aluminum alloy
- Multi-bus bar (MBB) technology
- Maximum static load up to 5400 Pa

Maximum Power Pmax (STC)	605 W
Maximum Power Current Imp (STC)	17.49 A
Short Circuit Current Isc (STC)	18.54 A
Maximum Power Voltage Vmp (STC)	34.60 V
Open Circuit Voltage Voc (STC)	41.70 V
Module efficiency factor (STC)	21.37 %

Maximum Power Pmax (NMOT)	458 W
Maximum Power Current Imp (NMOT)	14.22 A
Short Circuit Current Isc (NMOT)	14.96 A
Maximum Power Voltage Vmp (NMOT)	32.21 V
Open Circuit Voltage Voc (NMOT)	39.31 V

Power tolerance	3 %
-----------------	-----

© 2025, LEDVANCE GmbH. All rights reserved. Page 2 of 4

Cable length	1.4 m
Glass with anti-reflection coating	Yes
Colour backsheet	White
Colour cells	Dark blue
Colour frame	Silver
Front Glass	2.0 mm coated semi-tempered glass

TEMPERATURE RATINGS

Nominal operating cell temperature	44 °C
Temperature coefficient I _{sc}	0.040 %/K
Temperature coefficient P _{mp}	-0.340 %/K
Temperature coefficient U _{oc}	-0.250 %/K

OPERATING CONDITIONS

Maximum series fuse rating	30 A
Temperature range in operation	-40...+85 °C
Front Side Maximum Static Loading	5400 Pa
Rear Side Maximum Static Loading	2400 Pa
Reverse current load	30 A

EQUIPMENT / ACCESSORIES

- Product is delivered as a whole, no assembly required from customer
- MC4 EVO 2 connectors are fitted to the panel
- 3 bypass diodes are already installed in the panel

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	PV MODULE
	Declarations of conformity	CE Certificate PV Panels
	Product family datasheet	M585-605P60UM-SF-F3_EN

LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854137228	Shipping box 31	2,289 mm x 1,105 mm x 1,147 mm	928100.00 g	2901.16 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.


When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

Current-voltage curve of the module



Current-voltage curve of the module



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.