

PRODUCT DATASHEET

Decor Spot Neptune CLICK-SELECT White 2 Spot

DECOR SPOT NEPTUNE WHITE | Ceiling mounted luminaires with adjustable spotlights featuring selectable light sources via wall switch



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces
- Ceiling and wall surface mounting

Product benefits

- High-quality housing with matt white or matt black surface
- Easy mounting

Product features

- Luminaire family features four versions with up to 4 spot heads
- On/off switch on 1-head version for easy operation
- 3-step switch (click select) to turn on base and head light separately
- Adjustable heads



TECHNICAL DATA

Electrical data


Nominal wattage	20.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	90.000 mA
Inrush current time T _{h50}	321 µs
Max. number of luminaires per miniature circuit breaker B16	139
Max. number of luminaires per miniature circuit breaker C16	139
Power factor λ	> 0.5
Total harmonic distortion	< 70 %
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	715 lm
Luminous efficacy	36 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	6 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	101.00 °

Dimensions & Weight

Length	508.00 mm
Width	90.00 mm
Height	140.00 mm
Product weight	1260.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Adjustable	Yes
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR SPOT NEPTUNE
	Legal information	Safety insert G11219279
	Declarations of conformity	CE Declaration Decor Spot Pluto

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854471551	Folding box 1	132 mm x 172 mm x 573 mm	1785.00 g	13.01 dm ³
4099854471568	Shipping box 4	544 mm x 186 mm x 598 mm	7140.00 g	60.51 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.