

PRODUCT DATASHEET

LISOEV 330 SQ 19W 830 840 SF FLAT

SURFACE FLAT LIGHT SOURCES | Upgrade or replacement lightsource

Areas of application

- Suitable for SURFACE FLAT 19 W / 27 W



Product benefits

- 3000 K and 4000 K LEDs integrated
- Indoor use with high luminous efficacy of up to 140 lm/W
- High color consistency with SDCM 3
- Tool-free electrical connection with plug connectors
- Very homogenous light with a slight backlight effect
- Prepared for SURFACE FLAT SENSOR integration
- 5 years guarantee

Product features

- Type of protection: IP20
- Polycarbonate (PC) housing, PC-diffuser
- Lifetime (L80/B10): 100,000 h (at 25 °C), (L90/B10): 50,000 h (at 25 °C)
- Impact resistance: IK08
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- Indoor use only, not suitable for outdoor use




TECHNICAL DATA

Electrical data


Nominal wattage	16.0 W
Nominal voltage	30...40 V
Mains frequency	50...60 Hz
Nominal current	450 mA

Photometrical data


Luminous flux	2660 lm
Luminous efficacy	140 lm/W
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	3 sdcm
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °




LISOEV 330SQ 19W 830 SF FLAT
2490lm



LISOEV 330SQ 19W 840 SF FLAT
2660lm




LISOEV 330SQ 19W 830 SF FLAT
2490lm



LISOEV 330SQ 19W 840 SF FLAT
2660lm

Dimensions & Weight

Length	330.00 mm
Width	330.00 mm
Height	53.00 mm
Product weight	1038.00 g



LISOEV 330SQ 19W 830 840 SF
FLAT

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Ambient temperature range	-20...+45 °C
Temperature range at storage	-40...+80 °C
Type of protection	IP20
Dimmable	No
Mounting type	Surface

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Lifespan L80/B10 at 25 °C	100000 h
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	50000 h

Certificates & Standards

Standards	CE
Replaceable light source (EPREL)	Not replaceable

Additional product data

Added function	EVERLOOP / MULTI SELECT
----------------	-------------------------

EQUIPMENT / ACCESSORIES

- Connection wire for direct installation integrated

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	UI LISOEV SF FLAT
	Legal information	Legal Insert SF FLAT LISOEV
	Legal information	LISO Insert SF FLAT LISOEV
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	CE Declaration SF FLAT
	Declarations of conformity UKCA	UKCA Declaration SF FLAT
Photometric and lighting design files		Document name
	IES file (IES)	LISOEV 330SQ 19W 830 SF FLAT 2490lm
	IES file (IES)	LISOEV 330SQ 19W 840 SF FLAT 2660lm
	LDT file (Eulumdat)	LISOEV 330SQ 19W 830 SF FLAT 2490lm
	LDT file (Eulumdat)	LISOEV 330SQ 19W 840 SF FLAT 2660lm
	UGR file (UGR table)	LISOEV 330SQ 19W 830 SF FLAT 2490lm
	UGR file (UGR table)	LISOEV 330SQ 19W 840 SF FLAT 2660lm
	Light distribution curve type cone	LISOEV 330SQ 19W 830 SF FLAT 2490lm
	Light distribution curve type cone	LISOEV 330SQ 19W 840 SF FLAT 2660lm
	Light distribution curve type polar	LISOEV 330SQ 19W 830 SF FLAT 2490lm

Photometric and lighting design files	Document name
 Light distribution curve type polar	LISOEV 330SQ 19W 840 SF FLAT 2660lm

Tender texts	Document name
 Tender documents	SURFACE FLAT LIGHT SOURCES 330 SQ 19W 830 840 SF FLAT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854312250	Folding box 1	57 mm x 336 mm x 336 mm	1234.00 g	6.44 dm ³
4099854312267	Shipping box 6	355 mm x 353 mm x 358 mm	8065.00 g	44.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



SKU			SKU	
4099854312250	LISOEV 330SQ 830 840 SF FLAT	→	4099854312258	840 FLAT 830 840 SF 19W CIPS
4099854312258	LISOEV 330SQ 830 840 SF FLAT	→	4099854312259	840 FLAT 830 840 SF 19W CIPS
4099854312259	LISOEV 330SQ 830 840 SF FLAT	→	4099854312260	840 FLAT 830 840 SF 19W CIPS
4099854312260	LISOEV 330SQ 830 840 SF FLAT	→	4099854312261	840 FLAT 830 840 SF 19W CIPS
4099854312261	LISOEV 330SQ 830 840 SF FLAT	→	4099854312262	840 FLAT 830 840 SF 19W CIPS
4099854312262	LISOEV 330SQ 830 840 SF FLAT	→	4099854312263	840 FLAT 830 840 SF 19W CIPS
4099854312263	LISOEV 330SQ 830 840 SF FLAT	→	4099854312264	840 FLAT 830 840 SF 19W CIPS
4099854312264	LISOEV 330SQ 830 840 SF FLAT	→	4099854312265	840 FLAT 830 840 SF 19W CIPS
4099854312265	LISOEV 330SQ 830 840 SF FLAT	→	4099854312266	840 FLAT 830 840 SF 19W CIPS
4099854312266	LISOEV 330SQ 830 840 SF FLAT	→	4099854312267	840 FLAT 830 840 SF 19W CIPS
4099854312267	LISOEV 330SQ 830 840 SF FLAT	→	4099854312268	840 FLAT 830 840 SF 19W CIPS
4099854312268	LISOEV 330SQ 830 840 SF FLAT	→	4099854312269	840 FLAT 830 840 SF 19W CIPS
4099854312269	LISOEV 330SQ 830 840 SF FLAT	→	4099854312270	840 FLAT 830 840 SF 19W CIPS
4099854312270	LISOEV 330SQ 830 840 SF FLAT	→	4099854312271	840 FLAT 830 840 SF 19W CIPS
4099854312271	LISOEV 330SQ 830 840 SF FLAT	→	4099854312272	840 FLAT 830 840 SF 19W CIPS
4099854312272	LISOEV 330SQ 830 840 SF FLAT	→	4099854312273	840 FLAT 830 840 SF 19W CIPS
4099854312273	LISOEV 330SQ 830 840 SF FLAT	→	4099854312274	840 FLAT 830 840 SF 19W CIPS
4099854312274	LISOEV 330SQ 830 840 SF FLAT	→	4099854312275	840 FLAT 830 840 SF 19W CIPS
4099854312275	LISOEV 330SQ 830 840 SF FLAT	→	4099854312276	840 FLAT 830 840 SF 19W CIPS
4099854312276	LISOEV 330SQ 830 840 SF FLAT	→	4099854312277	840 FLAT 830 840 SF 19W CIPS
4099854312277	LISOEV 330SQ 830 840 SF FLAT	→	4099854312278	840 FLAT 830 840 SF 19W CIPS
4099854312278	LISOEV 330SQ 830 840 SF FLAT	→	4099854312279	840 FLAT 830 840 SF 19W CIPS
4099854312279	LISOEV 330SQ 830 840 SF FLAT	→	4099854312280	840 FLAT 830 840 SF 19W CIPS
4099854312280	LISOEV 330SQ 830 840 SF FLAT	→	4099854312281	840 FLAT 830 840 SF 19W CIPS
4099854312281	LISOEV 330SQ 830 840 SF FLAT	→	4099854312282	840 FLAT 830 840 SF 19W CIPS
4099854312282	LISOEV 330SQ 830 840 SF FLAT	→	4099854312283	840 FLAT 830 840 SF 19W CIPS
4099854312283	LISOEV 330SQ 830 840 SF FLAT	→	4099854312284	840 FLAT 830 840 SF 19W CIPS
4099854312284	LISOEV 330SQ 830 840 SF FLAT	→	4099854312285	840 FLAT 830 840 SF 19W CIPS
4099854312285	LISOEV 330SQ 830 840 SF FLAT	→	4099854312286	840 FLAT 830 840 SF 19W CIPS
4099854312286	LISOEV 330SQ 830 840 SF FLAT	→	4099854312287	840 FLAT 830 840 SF 19W CIPS
4099854312287	LISOEV 330SQ 830 840 SF FLAT	→	4099854312288	840 FLAT 830 840 SF 19W CIPS
4099854312288	LISOEV 330SQ 830 840 SF FLAT	→	4099854312289	840 FLAT 830 840 SF 19W CIPS
4099854312289	LISOEV 330SQ 830 840 SF FLAT	→	4099854312290	840 FLAT 830 840 SF 19W CIPS
4099854312290	LISOEV 330SQ 830 840 SF FLAT	→	4099854312291	840 FLAT 830 840 SF 19W CIPS
4099854312291	LISOEV 330SQ 830 840 SF FLAT	→	4099854312292	840 FLAT 830 840 SF 19W CIPS
4099854312292	LISOEV 330SQ 830 840 SF FLAT	→	4099854312293	840 FLAT 830 840 SF 19W CIPS
4099854312293	LISOEV 330SQ 830 840 SF FLAT	→	4099854312294	840 FLAT 830 840 SF 19W CIPS
4099854312294	LISOEV 330SQ 830 840 SF FLAT	→	4099854312295	840 FLAT 830 840 SF 19W CIPS
4099854312295	LISOEV 330SQ 830 840 SF FLAT	→	4099854312296	840 FLAT 830 840 SF 19W CIPS
4099854312296	LISOEV 330SQ 830 840 SF FLAT	→	4099854312297	840 FLAT 830 840 SF 19W CIPS
4099854312297	LISOEV 330SQ 830 840 SF FLAT	→	4099854312298	840 FLAT 830 840 SF 19W CIPS
4099854312298	LISOEV 330SQ 830 840 SF FLAT	→	4099854312299	840 FLAT 830 840 SF 19W CIPS
4099854312299	LISOEV 330SQ 830 840 SF FLAT	→	4099854312300	840 FLAT 830 840 SF 19W CIPS

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.