

# PRODUCT DATASHEET

## DL CMFT HE D200 P 25W ML 840 U19 WT

DOWNLIGHT COMFORT HIGH EFFICIENCY UGR<19 | Downlight luminaires with aluminum housing, very high luminous efficacy and low glare



PERFOR-  
MANCE  
CLASS

### Areas of application

- Direct replacement for recessed luminaires with fluorescent lamps
- Offices, conference rooms
- Reception areas, foyers, corridors, elevators

### Product benefits

- Energy savings thanks to high system efficacy: up to 145 lm/W
- Through wiring possible via included connector box
- High grade polycarbonate front frame for reduced overall luminaire weight
- Easy and quick installation thanks to connector box with 3-pole toolless terminal
- Uniform light with minimized glare thanks to included reflector and diffuser
- Highly versatile due to selectable power steps (Multi Lumen) via dip switches on the driver
- Well suited for retrofitting using an extension ring as separate accessory

### Product features

- Lifetime (L80/B10): up to 100,000 h (at 25 °C)
- Consistent lighting color  $\leq 3$  SDCM
- External driver with Multi Lumen function of up to 5220 lm
- Aluminum luminaires with 3 different cut-outs and mirror-finished reflector UGR  $\leq 19$
- Very homogenous light distribution and reduced glare of UGR  $\leq 19$




---

**TECHNICAL DATA****Electrical data**


|                                                             |                      |
|-------------------------------------------------------------|----------------------|
| Nominal wattage                                             | 25 W / 20 W / 15 W   |
| Nominal voltage                                             | 220...240 V          |
| Mains frequency                                             | 50...60 Hz           |
| Nominal current                                             | 113mA / 88mA / 75 mA |
| Inrush current                                              | 25.2 A               |
| Inrush current time $T_{h50}$                               | 90 $\mu$ s           |
| Max. number of luminaires per miniature circuit breaker B16 | 29                   |
| Max. number of luminaires per miniature circuit breaker C10 | 23                   |
| Max. number of luminaires per miniature circuit breaker C16 | 38                   |
| Power factor $\lambda$                                      | $\geq 0.90$          |
| Total harmonic distortion                                   | $\leq 20 \%$         |
| Protection class                                            | II                   |
| Surge capability (L-N)                                      | 1000 V               |

**Photometrical data**

|                                                |                             |
|------------------------------------------------|-----------------------------|
| Luminous flux                                  | 3625 lm / 2900 lm / 2175 lm |
| Total luminous flux of contained light sources | 2800 lm                     |
| Luminous efficacy                              | 145 lm/W                    |
| Color temperature                              | 4000 K                      |
| Light color (designation)                      | Cool White                  |
| Color rendering index Ra                       | > 80                        |
| Standard deviation of color matching           | 3 sdcn                      |
| Luminous intensity                             | 3800 lm / 3150 lm / 2500 lm |
| Low flicker                                    | Yes                         |
| Flickering metric (Pst LM)                     | <1                          |
| Stroboscope effect metric (SVM)                | <0.4                        |
| Photobiological safety group acc. to EN62778   | RG1                         |
| Photobiological safety group acc. to EN62471   | RG1                         |
| Beam angle                                     | 55 °                        |
| UGR                                            | 19                          |



DL CMFT HE D200 P 25W ML 840 U19 WT




DL CMFT HE D200 P 25W ML 840 U19 WT

Adjustable attributes

| Nominal wattage | Color temperature | Luminous flux | Luminous efficacy |
|-----------------|-------------------|---------------|-------------------|
| 25 W            | 4000 K            | 3625 lm       | 145 lm/W          |
| 20 W            | 4000 K            | 2900 lm       | 145 lm/W          |
| 15 W            | 4000 K            | 2175 lm       | 145 lm/W          |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 215.00 mm |
| Height         | 116.80 mm |
| Product weight | 550.00 g  |



DL CMFT HE D200 P 25W ML

Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | White              |
| Housing color                              | White              |
| RAL Color (most similar)                   | RAL 9003           |
| Body material                              | Aluminum           |
| Cover material                             | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |
| Mercury content                            | 0.0 mg             |

Application & Mounting

|                                        |                            |
|----------------------------------------|----------------------------|
| Ambient temperature range              | -20...+40 °C               |
| Temperature range at storage           | -20...+80 °C               |
| Type of connection                     | Screwless terminal, 3-Pole |
| Type of protection                     | IP44/IP20                  |
| Protection class IK (shock resistance) | IK03                       |
| Dimmable                               | No                         |
| Mounting location                      | Ceiling / Wall             |
| Application environment                | Indoor                     |
| Mounting diameter                      | 200 mm                     |
| Mounting depth                         | 117 mm                     |
| With light source                      | Yes                        |
| Replaceable light source               | No                         |

Lifespan

|                           |                        |
|---------------------------|------------------------|
| Lifespan L70/B50 at 25 °C | 100000 h <sup>1)</sup> |
|---------------------------|------------------------|

|                            |                        |
|----------------------------|------------------------|
| Lifespan L80/B10 at 25 °C  | 100000 h <sup>1)</sup> |
| Lifespan L80/B50 at 25 °C  | 100000 h               |
| Lifespan L90/B10 at 25 °C  | 62000 h                |
| Number of switching cycles | 100000                 |

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

|                             |                        |
|-----------------------------|------------------------|
| Output current              | 600mA / 500mA / 380 mA |
| ECG - Output ripple current | ≤ 10 %                 |
| Recommended control gear    | P0-PB42ML-4060         |

Emergency lighting

|                                           |        |
|-------------------------------------------|--------|
| Type of emergency operation test          | None   |
| Wattage in emergency operation mode       | 3 W    |
| Luminous flux in emergency operation mode | 370 lm |

Certificates & Standards

|                                                      |                             |
|------------------------------------------------------|-----------------------------|
| Standards                                            | ENEC / CE / EAC / CB / UKCA |
| Luminaire with limited surface temperature, "D sign" | No                          |
| Ball shot safe                                       | No                          |
| Replaceable light source (EPREL)                     | Not replaceable             |

Additional product data

|                |                              |
|----------------|------------------------------|
| Product remark | Available from December 2025 |
|----------------|------------------------------|

Accessories Optional

| Product image                                                                      | Product name          | EAN           |
|------------------------------------------------------------------------------------|-----------------------|---------------|
|  | DL CMFT FRAME D200 WT | 4099854500022 |
|  | DL CMFT FRAME D200 GY | 4099854500060 |

| Product image                                                                      | Product name              | EAN           |
|------------------------------------------------------------------------------------|---------------------------|---------------|
|    | DL CMFT FRAME D200 BK     | 4099854500046 |
|    | DL CMFT EXCH RING D200 GY | 4099854515460 |
|    | DL CMFT EXCH RING D200 BK | 4099854515347 |
|    | DL CMFT EXT RING D240 WT  | 4099854687631 |
|    | DL CMFT EXT RING D240 GY  | 4099854687693 |
|  | DL CMFT EXT RING D240 BK  | 4099854687662 |

EQUIPMENT / ACCESSORIES

- Security rope for luminaire included
- External control gear included
- Connector box with 3-pole terminal included
- Surface mounting frame options available
- Gray and black exchangeable rings available as separate accessory
- Extension rings are available as separate accessory
- Extension ring D190 for retrofitting D150 luminaire, extension ring D240 for retrofitting D200 luminaire

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.

DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                                                       |
|------------------------------------------------------------------------------------|----------------------------------------|---------------------------------------------------------------------|
|    | User instruction / safety instructions | DOWNLIGHT COMFORT HE                                                |
|    | Legal information                      | Legal Insert G11120030                                              |
|    | Legal information                      | Safety Insert G11207793                                             |
|    | Legal information                      | Informationstext 18 Abs 4 ElektroG                                  |
|    | Legal information                      | LSI G11253077 DL CMFT HE                                            |
|    | Declarations of conformity             | DL CMFT LUM                                                         |
|    | Declarations of conformity UKCA        | DL CMFT LUM                                                         |
|    | Certificates                           | ENEC Certificate DL CMFT HE                                         |
| Photometric and lighting design files                                              |                                        | Document name                                                       |
|  | IES file (IES)                         | DL CMFT HE D200 P 25W ML 840 U19 WT                                 |
|  | LDT file (Eulumdat)                    | DL CMFT HE D200 P 25W ML 840 U19 WT                                 |
|  | UGR file (UGR table)                   | DL CMFT HE D200 P 25W ML 840 U19 WT                                 |
|  | Light distribution curve type cone     | DL CMFT HE D200 P 25W ML 840 U19 WT                                 |
|  | Light distribution curve type polar    | DL CMFT HE D200 P 25W ML 840 U19 WT                                 |
| CAD/BIM files                                                                      |                                        | Document name                                                       |
|  | CAD STEP 3D                            | DL CMFT D200 MS U19                                                 |
| Tender texts                                                                       |                                        | Document name                                                       |
|  | Tender documents                       | DOWNLIGHT COMFORT HIGH EFFICIENCY UGR19 D200 P 25W ML 840 U19 WT-en |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4099854687020 | Folding box<br>1             | 235 mm x 235 mm x 140 mm             | 695.00 g     | 7.73 dm³  |
| 4099854687037 | Shipping box<br>8            | 490 mm x 490 mm x 310 mm             | 6560.00 g    | 74.43 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.