

# PRODUCT DATASHEET


## LED Spot Vase 2xG9 Brushed Nickel

LED Spot Vase | Surface mounted luminaires with adjustable G9 spotlights

---

### Areas of application

- Indoor applications



---

### Product benefits

- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

---

### Product features

- Luminaire family features five versions with up to 6 spot heads
- Housing surface made of brushed and chrome nickel
- Adjustable heads
- On/off switch on 1-head version for easy operation
- Diffuser made of glass




TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50/60 Hz      |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 340.00 mm |
| Width          | 90.00 mm  |
| Height         | 160.00 mm |
| Product weight | 540.00 g  |



LED SPOT VASE 2XG9

Materials & Colors

|                                            |                       |
|--------------------------------------------|-----------------------|
| Product color                              | Brushed nickel chrome |
| Housing color                              | Brushed nickel chrome |
| Body material                              | Steel                 |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                |

Application & Mounting

|                              |                             |
|------------------------------|-----------------------------|
| Ambient temperature range    | -20...+40 °C                |
| Temperature range at storage | -20...+80 °C                |
| Type of connection           | Terminal, 3-Pole (L, N, PE) |
| Dimmable                     | No                          |
| Mounting type                | Surface                     |
| Mounting location            | Wall / Ceiling              |
| Adjustable                   | Yes                         |
| With light source            | No                          |

|                          |     |
|--------------------------|-----|
| Replaceable light source | Yes |
| Holder designation       | G9  |

### Emergency lighting

|                                  |      |
|----------------------------------|------|
| Type of emergency operation test | None |
|----------------------------------|------|

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

### Additional product data

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Product remark        | Maximum bulb wattage: 5 W LED / Available from January 2026 |
| Number of illuminants | 2                                                           |

### Safety advice

- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name           |
|------------------------------------------------------------------------------------|----------------------------------------|-------------------------|
|  | User instruction / safety instructions | LED SPOT VASE G11239551 |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075853027 | Folding box<br>1             | 102 mm x 132 mm x 352 mm             | 674.00 g     | 4.74 dm <sup>3</sup>  |
| 4058075853034 | Shipping box<br>4            | 276 mm x 216 mm x 377 mm             | 3146.00 g    | 22.48 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.