

## PRODUCT DATASHEET

# Orbis Yummy 285MM 16W 830 Click DIM Black

Orbis Yummy | LED ceiling luminaire with metal frame of sandblasted stone



### Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)

### Product benefits

- Stylish and modern design
- Easy to install and use
- Long lifetime thanks to LED technology

### Product features

- Type of protection: IP20
- Lifetime up to 30,000 h
- Click-DIM version: dimmable in three steps by repeated switching
- Color temperature: 3,000 K (Warm White)
- Metal housing, PMMA cover



---

**TECHNICAL DATA****Electrical data**


|                                                             |                     |
|-------------------------------------------------------------|---------------------|
| Nominal wattage                                             | 16.00 W             |
| Nominal voltage                                             | 220...240 V         |
| Mains frequency                                             | 50...60 Hz          |
| Nominal current                                             | 125.000 mA          |
| Inrush current time $T_{h50}$                               | 3.19 $\mu$ s        |
| Max. number of luminaires per miniature circuit breaker B16 | 102                 |
| Max. number of luminaires per miniature circuit breaker C10 | 64                  |
| Max. number of luminaires per miniature circuit breaker C16 | 102                 |
| Power factor $\lambda$                                      | > 0.5               |
| Total harmonic distortion                                   | < 150 %             |
| Protection class                                            | I                   |
| Operating mode                                              | External LED driver |

**Photometrical data**

|                                              |               |
|----------------------------------------------|---------------|
| Luminous flux                                | 1000 lm       |
| Luminous efficacy                            | 62 lm/W       |
| Color temperature                            | 3000 K        |
| Light color (designation)                    | Warm White    |
| Color rendering index Ra                     | $\geq 80$     |
| Standard deviation of color matching         | $\leq 6$ sdcn |
| Photobiological safety group acc. to EN62778 | RG0           |
| Photobiological safety group acc. to EN62471 | RG0           |
| Beam angle                                   | 120 °         |

**Dimensions & Weight**

|                |           |
|----------------|-----------|
| Diameter       | 285.00 mm |
| Height         | 65.00 mm  |
| Product weight | 600.00 g  |



Materials & Colors

|                                            |         |
|--------------------------------------------|---------|
| Product color                              | Black   |
| Housing color                              | Black   |
| Body material                              | Metal   |
| Cover material                             | Plastic |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C  |

Application & Mounting

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ambient temperature range              | -20...+40 °C                |
| Temperature range at storage           | -20...+80 °C                |
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP20                        |
| Protection class IK (shock resistance) | IK03                        |
| Dimmable                               | Yes                         |
| Mounting type                          | Surface                     |
| Application environment                | Indoor                      |
| With light source                      | Yes                         |
| Replaceable light source               | No                          |

Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 50000 h <sup>1)</sup> |
| Number of switching cycles | 25000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA       |
| Luminaire with limited surface temperature, "D sign" | No              |
| Ball shot safe                                       | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

## EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

## Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

## DOWNLOAD DATA

|                                                                                    | Documents and certificates             | Document name                                                                |
|------------------------------------------------------------------------------------|----------------------------------------|------------------------------------------------------------------------------|
|  | User instruction / safety instructions | ORBIS YUMMY                                                                  |
|  | Legal information                      | Safety insert G11219601                                                      |
|  | Declarations of conformity             | ORBIS ALISON ORBIS WOODBURRY ORBIS ALICIA ORBIS YUMMY ORBIS LIVIA ORBIS ALVA |
|  | Declarations of conformity UKCA        | ORBIS ALISON ORBIS WOODBURRY ORBIS ALICIA ORBIS YUMMY ORBIS LIVIA ORBIS ALVA |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854450907 | Folding box<br>1             | 77 mm x 307 mm x 308 mm              | 930.00 g     | 7.28 dm <sup>3</sup>  |
| 4099854450914 | Shipping box<br>6            | 478 mm x 323 mm x 333 mm             | 5580.00 g    | 51.41 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.