

## PRODUCT DATASHEET

### Floodlight Essential 30W 4000K

Essentials Floodlights | Essential Floodlights for basic user purposes



#### Areas of application

- Outdoor
- Building facades

#### Product benefits

- IP65 protection is suitable for outdoor application
- White satin-frosted diffuser for uniform glare-free light

#### Product features

- IP65 outdoor floodlight
- Adjustable light angle



TECHNICAL DATA

Electrical data


|                                                             |         |
|-------------------------------------------------------------|---------|
| Nominal wattage                                             | 30.00 W |
| Inrush current time T <sub>h50</sub>                        | 84 µs   |
| Max. number of luminaires per miniature circuit breaker B16 | 94      |
| Max. number of luminaires per miniature circuit breaker C16 | 94      |
| Power factor λ                                              | ≥0.90   |
| Total harmonic distortion                                   | < 20 %  |

Photometrical data

|                                                |            |
|------------------------------------------------|------------|
| Total luminous flux of contained light sources | 2850 lm    |
| Light color (designation)                      | Cool White |
| Standard deviation of color matching           | 6 sdcn     |
| Photobiological safety group acc. to EN62778   | RG1        |
| Photobiological safety group acc. to EN62471   | RG1        |
| UGR                                            | < 28       |

Dimensions & Weight

|                |          |
|----------------|----------|
| Product weight | 510.00 g |
| Cable length   | 300 mm   |



FL ESSENTIAL 30W

Materials & Colors

|               |       |
|---------------|-------|
| Product color | Black |
| Housing color | Black |

|                                            |          |
|--------------------------------------------|----------|
| Body material                              | Aluminum |
| Cover material                             | Glass    |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C   |

### Application & Mounting

|                                        |              |
|----------------------------------------|--------------|
| Ambient temperature range              | -30...+40 °C |
| Temperature range at storage           | -30...+80 °C |
| Protection class IK (shock resistance) | IK04         |
| Dimmable                               | No           |
| Mounting type                          | Surface      |
| Adjustable                             | Yes          |
| With light source                      | Yes          |
| Replaceable light source               | No           |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 25000 h <sup>1)</sup> |
| Number of switching cycles | 25000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA       |
| Luminaire with limited surface temperature, "D sign" | No              |
| Ball shot safe                                       | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

### Additional product data

|                       |       |
|-----------------------|-------|
| Number of illuminants | empty |
|-----------------------|-------|

### EQUIPMENT / ACCESSORIES

- Connection cable included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's

reach.

– Check wall-ceiling for suitability. If uncertain, seek professional advice.

## DOWNLOAD DATA

| Documents and certificates                                                        |                                        | Document name                      |
|-----------------------------------------------------------------------------------|----------------------------------------|------------------------------------|
|   | User instruction / safety instructions | FL ESSENTIAL_SENSOR                |
|   | Legal information                      | Safety insert G11220429            |
|   | Legal information                      | Informationstext 18 Abs 4 ElektroG |
|   | Declarations of conformity             | CE Declaration FL Essential        |
|   | Declarations of conformity             | FL ESSENTIAL                       |
|   | Declarations of conformity UKCA        | FLOODLIGHT                         |
|  | Declarations of conformity UKCA        | FL ESSENTIAL                       |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854429774 | Folding box<br>1             | 40 mm x 131 mm x 195 mm              | 555.00 g     | 1.02 dm <sup>3</sup>  |
| 4099854429781 | Shipping box<br>20           | 408 mm x 214 mm x 287 mm             | 11100.00 g   | 25.06 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.