

PRODUCT DATASHEET

SMART ZB P40 D 4.9W 220V FR E14

SMART+ Classic Dimmable | Classic bulb shape with Zigbee technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

Product features

- Control via compatible smart home system (gateway and app)
- Control via voice control available: Google Assistant or Amazon Alexa, depending on the smart home system in use
- Network protocol: ZigBee 3.0
- Dimmable
- Lifetime: up to 20,000 h
- For full functionality connection to a compatible smart home System (gateway and app) required




TECHNICAL DATA

Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	220...240 V
Nominal current	38 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	40 W
Operating mode	AC Mains

Photometrical data

Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤6 sdc _m
Nominal luminous flux	470 lm
Luminous flux	470 lm
Luminous efficacy	95 lm/W
Color temperature	2700 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4



Everlight 67-23ST KKE 2700K

Light technical data

Beam angle	200 °
Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s

Dimensions & Weight



Product weight	23.00 g
Diameter	47.00 mm
Maximum diameter	47 mm
Length	92.00 mm
Width	47.00 mm
Height	47.00 mm
Outer bulb [PICOS]	P40

Lifespan

Number of switching cycles	100000
Lifespan	20000 h
Lumen maintenance at end of service lifetime	0.95

Colors & materials

Product color	White
Housing color	White
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E14

Capabilities

Dimmable	Yes ¹⁾
----------	-------------------

1) Via App

Certificates & Standards

Energy efficiency class	F ¹⁾
Energy consumption	5.00 kWh/1000h
Standards	CE / EAC / UKCA
Type of protection	IP20

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	≤ 0.5 W
Networked standby power for CLS	<0.5
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.42
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0 W
LED light source replaces a fluorescent light source	No
EPREL ID	1160673
Model number	AC41287

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	SMARTZB 220-240V DIMFS1
	Declarations of conformity	SMART ZB DIM A60 / B40 / P40 / PAR16
	EU Data Act	SMART ZigBee Lamps and Luminaires
Photometric and lighting design files		Document name
	Spectral power distribution	Everlight 67-23ST KKE 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854460777	Folding box 1	56 mm x 78 mm x 82 mm	49.00 g	0.36 dm ³
4099854460784	Shipping box 4	162 mm x 122 mm x 96 mm	268.00 g	1.90 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.