

PRODUCT DATASHEET

SMART+ ZIGBEE Tunable White Classic A60 9W E27

SMART+ ZIGBEE Tunable White | Classic lamps with Zigbee technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

Product features

- Controllable via compatible smart home system (gateway and app)
- Control via voice control available: Google Assistant or Amazon Alexa, depending on the smart home system in use
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Network protocol: ZigBee 3.0
- Dimmable
- Lifetime: up to 20,000 h
- For full functionality connection to a compatible smart home System (gateway and app) required




TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220...240 V
Nominal current	55 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	60 W
Operating mode	AC Mains

Photometrical data

Light color (designation)	Tunable White
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤6 sdcn
Nominal luminous flux	806 lm
Luminous flux	806 lm
Luminous efficacy	89 lm/W
Adjustable color temperature	2700...6500 K
Color temperature	2700...6500 K
Color rendering index Ra	≥80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4



Everlight 67-23ST KKE 2700K

Light technical data

Beam angle	200 °
------------	-------

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s

Dimensions & Weight



Product weight	55.00 g
Diameter	60.00 mm
Maximum diameter	60 mm
Length	112.00 mm
Width	60.00 mm
Height	60.00 mm
Outer bulb [PICOS]	A60

Lifespan

Number of switching cycles	100000
Lifespan	20000 h
Lumen maintenance at end of service lifetime	0.95

Colors & materials

Product color	White
Housing color	White
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E27

Capabilities

Dimmable	Yes ¹⁾
Compatible smart home technology	Amazon Alexa / Google Home

¹⁾ Via App

Certificates & Standards

Energy efficiency class	F ¹⁾
Energy consumption	9.00 kWh/1000h
Standards	CE / EAC / UKCA
Type of protection	IP20

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)






Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	0 W
Networked standby power for CLS	<0.5
Claim of equivalent power	Yes
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	>0.5
LED light source replaces a fluorescent light source	No
EPREL ID	1160668
Model number	AC41282

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	SMARTZB 220-240V4X1
	Declarations of conformity	SMART ZB TW A60/B40/P40/PAR16_ RGBW PAR16
	Declarations of conformity UKCA	SMART ZB TW A60/B40/P40/PAR16_ RGBW PAR16
	EU Data Act	SMART ZigBee Lamps and Luminaires
Photometric and lighting design files		Document name
	Spectral power distribution	Everlight 67-23ST KKE 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854460234	Folding box 1	61 mm x 78 mm x 114 mm	78.00 g	0.54 dm ³
4099854460241	Shipping box 4	164 mm x 130 mm x 128 mm	392.00 g	2.73 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.