

PRODUCT DATASHEET P CLAS A 150 21 W/2700 K E27

PARATHOM® CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

Product features

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Long lifetime up to 25,000 h
- Good quality of light; color rendering index $R_{a:} \geq$ 80; constant chromaticity



TECHNICAL DATA

Electrical data

Nominal wattage	21 W
Construction wattage	21.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	150 W
Nominal current	100 mA
Type of current	AC
Inrush current	4.7 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	45
Max. lamp number on MCB B16 A	72
Power factor λ	> 0.90

Photometrical data

Luminous flux	2452 lm
Nominal useful luminous flux 90°	2452 lm
Luminous efficacy	116 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	200 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	143.00 mm
Diameter	67.00 mm
Maximum diameter	67 mm

Product weight	208.00 g
Temperatures & operating conditions	
Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	109 °C
Lifespan	
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	Yes
Certificates & Standards	
Energy efficiency class	A+ 1)
Energy consumption	21.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0
1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E	E (lowest efficiency)
Country-specific categorizations	
ILCOS	DRAA/F-21/827-220-240-E27-60
Order reference	LEDPCLA150D 21W
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	E27

Length	143.00 mm
Height	67.00 mm
Width	67.00 mm

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	Declarations of conformity	Declaration of Conformity LED Classic A, B, P, Stick Lamps	
	Photometric and lighting design files	Document name	
	IES file (IES)	AC10701_CLA150D 21W 230VFR E27	
	LDT file (Eulumdat)	AC10701_CLA150D 21W 230VFR E27	
	Light distribution curve type polar	LEDPCLA150D FR 21W 827 230V E27 FS1OSRAM	
	Light distribution curve type polar	LEDPCLA150D 21W 827 230VFR E27 FS1 OSRAM	
	Light distribution curve type polar	LEDPCLA150D 21W 827 230VFR E27 FS1 OSRAM	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075292611	Folding box	67 mm x 67 mm x 145 mm	233.00 g	0.65 dm ³
4058075292628	Shipping box 10	348 mm x 145 mm x 159 mm	2457.00 g	8.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.