

PRODUCT DATASHEET

SST PAR 16 35 36 ° 3.7 W/2700 K GU10

LED SUPERSTAR PAR16 | Dimmable LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- High color consistency thanks to narrow binning
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Ideal for economical spotlighting

Product features

- LED alternative to conventional high voltage lamps
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps




TECHNICAL DATA

Electrical data

Nominal wattage	3.7 W
Construction wattage	3.70 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	35 W
Nominal current	17 mA
Type of current	AC
Inrush current	2 A
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Max. lamp number on MCB B10 A	237
Max. lamp number on MCB B16 A	379
Power factor λ	> 0.70

Photometrical data

Luminous intensity	630 cd
Luminous flux	230 lm
Nominal useful luminous flux 90°	230 lm
Luminous efficacy	62 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥90
Light color	927
Standard deviation of color matching	≤5 sdcn
Rated peak intensity	630 cd
Rated LLMF at 6,000 h	0.80



Everlight 67-23ST HKE 2700K

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	55.00 mm
Diameter	51.00 mm
Maximum diameter	51 mm
Product weight	48.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	85 °C

Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G 1)
Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC

Photobiological safety group acc. to EN62778	RG0
--	-----

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

ILCOS	DRPAR-3,1/827-220-240-GU10-50/36
Order reference	LSPAR16D35363,7

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	GU10
Correlated colour temperature type	SINGLE_VALUE
Length	55.00 mm
Height	51.00 mm
Width	51.00 mm
EPREL ID	1402936,1403124
Model number	AC16509,AC26508

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	EC Declaration of Conformity Self-ballasted LED lamp

Photometric and lighting design files		Document name
	Spectral power distribution	Everlight 67-23ST HKE 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899390133	Blister 1	50 mm x 140 mm x 120 mm	59.00 g	0.84 dm³
4052899390140	Shipping box 10	290 mm x 254 mm x 134 mm	671.00 g	9.87 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
 - For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
 - For Guarantee see www.ledvance.com/guarantee
-

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.