

## PRODUCT DATASHEET

### LED STAR CLAS A 60 FR 7 W/2700 K B22d

LED Retrofit CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Lower energy consumption than incandescent or halogen lamps
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time

#### Product features

- Professional LED lamps for line voltage
- Not dimmable
- Lifetime up to 15,000 h
- Beam angle: up to 300°
- Lamp made of glass



- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity


TECHNICAL DATA

Electrical data

|                                        |             |
|----------------------------------------|-------------|
| Nominal wattage                        | 7 W         |
| Construction wattage                   | 7.00 W      |
| Nominal voltage                        | 220...240 V |
| Claimed equiv. conventional lamp power | 60 W        |
| Nominal current                        | 52 mA       |
| Type of current                        | AC          |
| Inrush current                         | 6.3 A       |
| Operating frequency                    | 50...60 Hz  |
| Mains frequency                        | 50...60 Hz  |
| Max. lamp number on MCB B10 A          | 96          |
| Max. lamp number on MCB B16 A          | 154         |
| Power factor $\lambda$                 | > 0.50      |

Photometrical data

|                                         |                     |
|-----------------------------------------|---------------------|
| Luminous flux                           | 806 lm              |
| Luminous efficacy                       | 115 lm/W            |
| Lumen main.fact.at end of nom.life time | 0.70                |
| Light color (designation)               | Warm White          |
| Color temperature                       | 2700 K              |
| Color rendering index Ra                | ≥80                 |
| Light color                             | 827                 |
| Standard deviation of color matching    | ≤6 sdc <sub>m</sub> |



EPREL data spectral diagram PROF  
LEDr 2700K

Light technical data

|            |       |
|------------|-------|
| Beam angle | 300 ° |
|------------|-------|

|                     |          |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

### Dimensions & Weight

|                  |           |
|------------------|-----------|
| Overall length   | 104.00 mm |
| Diameter         | 60.00 mm  |
| Maximum diameter | 60 mm     |
| Product weight   | 29.00 g   |

### Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 62 °C        |

### Lifespan

|                                              |        |
|----------------------------------------------|--------|
| Number of switching cycles                   | 100000 |
| Lumen maintenance at end of service lifetime | 0.70   |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90 |

### Additional product data

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base (standard designation) | B22d                                                                                                                                                                                                                                                                                                                                         |
| Mercury content             | 0.0 mg                                                                                                                                                                                                                                                                                                                                       |
| Mercury-free                | Yes                                                                                                                                                                                                                                                                                                                                          |
| Design / version            | Frosted                                                                                                                                                                                                                                                                                                                                      |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|                         |      |
|-------------------------|------|
| Energy efficiency class | E 1) |
|-------------------------|------|

|                                              |                |
|----------------------------------------------|----------------|
| Energy consumption                           | 7.00 kWh/1000h |
| Type of protection                           | IP20           |
| Standards                                    | CE             |
| Photobiological safety group acc. to EN62778 | RG0            |

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

### Country-specific categorizations

|                 |                              |
|-----------------|------------------------------|
| ILCOS           | DRAA/F-7/827-220/240-B22d-60 |
| Order reference | LEDSCLA607W/827              |

### Energy labelling regulation data acc EU 2019/2015

|                                                     |                        |
|-----------------------------------------------------|------------------------|
| Light source cap-type (or other electric interface) | B22d                   |
| Correlated colour temperature type                  | SINGLE_VALUE           |
| Length                                              | 104.00 mm              |
| Height                                              | 60.00 mm               |
| Width                                               | 60.00 mm               |
| EPREL ID                                            | 1402911,523073,1361316 |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### DOWNLOAD DATA

| Documents and certificates                                                          |                             | Document name                               |
|-------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------|
|   | Declarations of conformity  | LED lamps CLA,B,G,P                         |
|   | Declarations of conformity  | LED CLASSIC                                 |
| Photometric and lighting design files                                               |                             | Document name                               |
|  | Spectral power distribution | EPREL data spectral diagram PROF LEDr 2700K |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075114913 | Folding box<br>1             | 60 mm x 60 mm x 145 mm               | 46.00 g      | 0.52 dm <sup>3</sup> |
| 4058075435407 | Folding box<br>2             | 61 mm x 121 mm x 145 mm              | 82.00 g      | 1.07 dm <sup>3</sup> |
| 4058075605022 | Shipping box<br>6            | 202 mm x 134 mm x 120 mm             | 340.00 g     | 3.25 dm <sup>3</sup> |
| 4058075605992 | Shipping box<br>6            | 202 mm x 134 mm x 120 mm             | 360.00 g     | 3.25 dm <sup>3</sup> |
| 4058075114920 | Shipping box<br>10           | 322 mm x 134 mm x 120 mm             | 582.00 g     | 5.18 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.