

PRODUCT DATASHEET

DALI PRO PB Coupler

DALI PRO PB Coupler | Control units for light management systems



Areas of application

- Classrooms
- Conference rooms
- Suitable for installation in flush-type boxes
- Production and assembly facilities
- Individual offices

Product benefits

- Power supply from DALI
- Standard pushbuttons/switches can be used

Product features


- DALI pushbutton coupler
- 4 floating inputs

TECHNICAL DATA

Electrical data

| | |
|-----------------|--------|
| Nominal wattage | 1.00 W |
| Nominal voltage | 20 V |
| Mains frequency | 0 Hz |

Dimensions & Weight



| | |
|----------------|----------|
| Length | 42.00 mm |
| Width | 42.00 mm |
| Height | 20.00 mm |
| Product weight | 22.00 g |

Temperatures & operating conditions

| | |
|---------------------------|------------|
| Ambient temperature range | 0...+50 °C |
|---------------------------|------------|

Additional product data

| | |
|---------------------------|---|
| Number of control outputs | 1 |
|---------------------------|---|

Capabilities

| | |
|-------------------|------|
| Dimmable | No |
| Dimming interface | DALI |



Certificates & Standards

| | |
|--------------------|------|
| Protection class | II |
| Type of protection | IP20 |

EQUIPMENT / ACCESSORIES

- Can be used with DALI Professional or DALIeco light control system

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|---|
|  | User instruction / safety instructions | 334697_Technical instructions |
|  | Declarations of conformity | 334811_Declaration of conformity – DALI PRO CONT-4 – DALI PRO PB Coupler – DALI PRO Sen |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4008321496461 | Folding box 1 | 93 mm x 40 mm x 80 mm | 43.00 g | 0.30 dm ³ |
| 4008321543134 | Shipping box 20 | 255 mm x 166 mm x 258 mm | 1033.00 g | 10.92 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.