

PRODUCT DATASHEET

TruSys® PFM VN 35 W/4000 K

TruSys® PERFORMANCE VERY NARROW | Luminaire inserts with very narrow light distribution



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, garages, hardware stores

Product benefits

- Very directed light distribution for high rack warehouses
- Easy installation, no tools required for connection
- Energy saving and cost-effective
- Flexible application due to a range of different lumen packages and beam angles
- Rows of up to 57 (On-Off) / 66 (DALI) luminaires possible
- Versions with DALI ECG available

Product features

- Beam angle very narrow: 30°
- Click into place solution with smart click buttons
- Luminous efficacy: up to 160 lm/W
- Fixed luminaire taps
- Lumen package 5600 lm, 8000 lm, 11200 lm
- Steel-sheet housing
- Lens material: PMMA




- Type of protection: IP20
- Common family design with LEDVANCE
- Lifetime (L80/B10): up to 60,000 h

TECHNICAL DATA**Electrical data**


Nominal wattage	35.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	190 mA
Inrush current	25 A
Inrush current time T_{h50}	220 μ s
Max. number of luminaires per miniature circuit breaker B16	13
Max. number of luminaires per miniature circuit breaker C10	12
Max. number of luminaires per miniature circuit breaker C16	19
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Integrated LED driver

Photometrical data


Luminous flux	5600 lm
Luminous efficacy	160 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 3 sdc _m
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG1
Beam angle	30 °
UGR	21




TRUSYS PFM 35W 4000K VN 4x1
EUE LEDV



TRUSYS PFM 35W 4000K VN 4x1
EUE LEDV




TRUSYS PFM 35W 4000K VN



TRUSYS PFM 35W 4000K VN

Dimensions & Weight

Length	1500.00 mm
Width	66.80 mm
Height	39.40 mm
Product weight	1660.00 g



Materials & Colors

Product color	White
Housing color	White

Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-25...+40 °C
Type of connection	Plug-In connection
Type of protection	IP20
Protection class IK (shock resistance)	IK04
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Mounting rail
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	65000 h ¹⁾
Lifespan L80/B10 at 25 °C	60000 h ¹⁾
Lifespan L80/B50 at 25 °C	60000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	420 mA
ECG - Output ripple current	< 20 %

Certificates & Standards

Standards	CE / CB / ENEC / EAC
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Number of illuminants	-
-----------------------	---

EQUIPMENT / ACCESSORIES

– Mounting rail with fixed integrated 5- and 8-pole cable

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	UI_Trusys® TRUNKING SYSTEM PFM ON/OFF
	Legal information	LS Insert Trusys PFM
	Declarations of conformity	TRUSYS PFM
Photometric and lighting design files		Document name
	IES file (IES)	TRUSYS PFM 35W 4000K VN
	LDT file (Eulumdat)	TRUSYS PFM 35W 4000K VN
	ULD file (DIALux)	TRUSYS PFM 35W-4000K VN
	UGR file (UGR table)	TRUSYS PFM 35W 4000K VN
	Light distribution curve type cone	TRUSYS PFM 35W 4000K VN 4x1 EUE LEDV
	Light distribution curve type cone	TRUSYS PFM 35W 4000K VN
	Light distribution curve type polar	TRUSYS PFM 35W 4000K VN
	Light distribution curve type polar	TRUSYS PFM 35W 4000K VN 4x1 EUE LEDV
CAD/BIM files		Document name
	CAD STEP 3D	TRUSYS PFM INSERT
Tender texts		Document name
	Tender documents	TruSys PERFORMANCE VERY NARROW 35 W4000 K-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075398696	Folding box 1	108 mm x 1,534 mm x 102 mm	1835.00 g	16.90 dm³
4058075398702	Shipping box 4	1,547 mm x 218 mm x 231 mm	8133.00 g	77.90 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.