



## PRODUCT DATASHEET

### ENDURA Classic Tradition Up Sensor E27

### Gold

ENDURA® CLASSIC TRADITION ALU | Timeless lantern shape with aluminum housing



#### Areas of application

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

#### Product benefits

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

#### Product features

- Die-cast aluminum housing
- Diffuser made of clear polycarbonate
- Available with and without motion sensor
- Available as wall and bollard luminaires
- Suitable for smart applications thanks to compatibility with SMART+ lamps




TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 230.00 mm |
| Width          | 170.00 mm |
| Height         | 280.00 mm |
| Product weight | 600.00 g  |



ENDURA CLASSIC TRAD UPSENS  
ALU E27 GD

Materials & Colors

|                 |            |
|-----------------|------------|
| Product color   | Black/Gold |
| Housing color   | Black/Gold |
| Body material   | Aluminum   |
| Mercury content | 0.0 mg     |

Application & Mounting

|                              |                |
|------------------------------|----------------|
| Ambient temperature range    | -20...+40 °C   |
| Temperature range at storage | -20...+85 °C   |
| Type of connection           | Screw terminal |
| Type of protection           | IP44           |
| Dimmable                     | No             |
| Mounting type                | Surface        |
| Application environment      | Outdoor        |

|                          |     |
|--------------------------|-----|
| With light source        | No  |
| Replaceable light source | No  |
| Holder designation       | E27 |

### Sensor

|                        |                        |
|------------------------|------------------------|
| Type of sensor         | Motion / Light         |
| Sensor technology      | Passive infrared (PIR) |
| Sensor detection angle | 80 °                   |

### Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA / EAC |
| Luminaire with limited surface temperature, "D sign" | No              |

### Additional product data

|                       |                            |
|-----------------------|----------------------------|
| Product remark        | Maximum bulb wattage: 60 W |
| Number of illuminants | 1                          |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                |
|------------------------------------------------------------------------------------|----------------------------------------|------------------------------|
|  | User instruction / safety instructions | ENDURA CLASSIC TRADITIONAL W |
|  | Legal information                      | Safety insert G11219578      |
|  | Declarations of conformity             | ENDURA CLASSIC               |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854452437 | Folding box<br>1             | 181 mm x 239 mm x 292 mm             | 1 120.00 g   | 12.63 dm <sup>3</sup> |
| 4099854452444 | Shipping box<br>4            | 493 mm x 377 mm x 312 mm             | 4 480.00 g   | 57.99 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.